

Kapur Mahal, 2nd Floor, Block No. 18-B, 65, Marine Drive, Mumbai – 400020

T +91-22-22078362 M: +91-98205 30635 E: sales@panchemcorp.com

SODIUM BUTYRATE - COATED 90%

Sr. No.	Parameter	Specification	Test Method Reference
1	Appearance	Fine Granules	Visual
2	Color	White to light brown	Visual
3	Odor	Faint butyric acid smell	Visual
4	pH (5%w/w Aq. soln.)	7.0 – 14.0	In House Method
5	Water content (%w/w)	Max. 5.0%	In House Method
6	Density	0.5 - 0.7 g/cc	In house Method
7	Crude Fat (%w/w)	Max. 10.0%	---
8	Particle size (%w/w)	+12 mesh ASTM : 100% pass	Using Standard Test Sieves
		-35 mesh ASTM : 10%	Using Standard Test Sieves
9	Iron (Fe)	Max. 100 ppm	In House Method
10	Purity (%w/w) on dried basis	Min. 90.0%	In House Method
11	Heavy Metal as Lead (Pb)	Max. 30 ppm	AAS
12	Arsenic (As)	Max. 2 ppm	AAS
13	Cadmium (Cd)	Max. 2 ppm	AAS
14	Mercury (Hg)	Max. 2 ppm	AAS
15	Fluoride (F)	Max. 30 ppm	USP

Standard Packaging

- 25 Kg / 50 Lbs Heavy Duty LDPE Bags.

Application

- Supplement in the Animal feed and nutrition industry - Improves Gut Health, promotes Intestinal Development, controls Enteric Pathogens and promotes overall growth in animals.
 - Less Odor & Slow Targeted Release.